

Gryphon GFS4500 Series	
Gryphon I GFE4590, 2D, MP, OEM Decoded Scan Engine, Red illumination, 5-14V, USB/RS232, 12 PIN CONNECTOR	GFE4590-RED
Gryphon I GFS4520, 2D, MP, Red illumination, 5V, USB-only, microUSB connector, Black	GFS4520-BK-RED
Gryphon I GFS4520, 2D, MP, White illumination, 5V, USB-only, microUSB connector, Black	GFS4520-BK-WHT
Gryphon I GFS4520, Kit, 2D, MP, Red illumination, 5V, USB-only, microUSB connector, Black (Kit includes Scanner and USB Cable 94A051968)	GFS4520-BKK1-RED
Gryphon I GFS4520, Kit, 2D, MP, White illumination, 5V, USB-only, microUSB connector, Black (Kit includes Scanner and USB Cable 94A051968)	GFS4520-BKK1-WHT
Gryphon I GFS4550, 2D, MP, Red illumination, 5-14V, RS232-only, 2m cable DB9 connector, Black	GFS4550-BKK2-RED
Gryphon I GFS4590, 2D, MP, Red illumination, 5-14V, USB/RS232, 10cm RJ socket to adapt normal handheld cables , Black	GFS4590-BK-RED

EASEOFCARE AGREEMENTS	
Gryphon GFS4500 EofC 2 Days Comp 1 Yr, R	ZSC2GFS45R1
Gryphon GFS4500 EofC 2 Days Comp 5 Yr	ZSC2GFS4551
Gryphon GFS4500 EofC 5 Days, 1 Yr, Renew	ZSN5GFS45R1
Gryphon GFS4500 EofC 5 Days, 5 Years	ZSN5GFS4551
Gryphon GFS4500 EofC Ovrnht Rplce 1 Yr R	ZSC1GFS45R1
Gryphon GFS4500 EofC Ovrnht Rplcmnt 5 Yr	ZSC1GFS4551

CABLES	
Cable from Micro USB (device or dock) to USB. Device works as client. 2m straight cable.	94A051968
Cable, RS-232, 12' Coiled (For Magellan)	90G001095
Cable, RS-232, 9P, Female, Coiled, CAB-362, External Power, 6 ft.	90A051330
Cable, RS-232, 9P, Female, Coiled, CAB-408 (Power available on pin 9 of the connector or through external power supply), 6 ft.	90A051891
Cable, RS-232, 9P, Female, Straight, CAB-327, Requires External Power, 6 ft.	90G000008
Cable, RS-232, 9P, Female, Straight, CAB-350 (Power Supply available on pin 9 of the connector or through external power supply), 6 ft.	90A051230
Cable, RS-232, 9P, Male, Beetle POS, Straight, CAB-389, Power Off Terminal, 6.5 ft.	90A051710
Cable, RS-232, DCE, 9P, Extended Power-Power off Terminal, 4 Meters	90A052086

Cable, RS-232,RJ to RJ, Coiled, 6' (For Magellan Aux Port)	90G001092
Cable, USB, Power Conn, Straight, Power off terminal, 2 Meters, CAB-413E2	90A052101
Cable, USB, Type A, Coiled, Power off terminal, 2 Meters, CAB-424E	90A052100
Cable, USB, Type A, Enhanced, Coiled, Power Off Terminal, 5 Meters	90A052066
Cable, USB, Type A, Enhanced, Straight, Power Off Terminal, 2M (USB Certified)	90A052065
Cable, USB, Type A, External Power, High Current, PVCW, Straight, 1.2M, Black (for use with WLC4X90 Wireless Charging Base Station)	90A052361
Cable, USB, Type A, External Power, High Current, PVCW, Straight, 3M, Black (for use with WLC4X90 Wireless Charging Base Station)	90A052356
Cable, USB, Type A, PVCW, Straight, 2M, Black	90A052258
Cable, USB, Type A, PVCW, Straight, 2M, White	90A052278
Cable, USB, Type A, TPUW, Coiled, Power off Terminal, 5M, Black	90A052289
Cable, USB, Type A,TPUW, Coiled, 2.4m, Black	90A052285
Cable, USB, Type C, High Current, PVCW, Straight, 1.2M, Black (for use with WLC4190 Wireless Charging Base Station)	90A052360
Cable, USB, Type C, High Current, PVCW, Straight, 3M, Black (for use with WLC4190 Wireless Charging Base Station)	90A052355
Cable, USB, Type C, PVCW, Coiled 2.4M, Black	90A052354
Cable, USB, Type C, PVCW, Straight, 2M, Black	90A052352
Cable, USB, Type C, PVCW, Straight, 2M, White	90A052353
Cable, USB+PWR,TPUW, Straight, 2M, Black	90A052302
CABLE,RS232,DB9,12 PIN CONNECTOR,2M,for GFE4500	90A052318
CABLE,USB,12 PIN CONNECTOR,2M, for GFE4500	90A052324
CBL USB2.0 A/M TO MICRO B/M,3M,BK,SH6382	90A052403
CBL USB2.0 A/M TO MICRO B/M,5M,BK,SH6382	90A052404

MOUNTS/STANDS

KIOSK MOUNTING ADAPTER GFS4500 BLACK

KMA-4500-BK

Mounting Adapter to replicate the GFS4400 fixing holes

MA-4500-BK